



ARTEL


www.artelpelletkachel.nl

**NIEUW IN HET
ASSORTIMENT**



CV Moederhaard

Classic



Artel Classic Idro		15 kW		20 kW		24 kW		28 kW		32 kW	
	Eenheid	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
 Vermogen	kW	15	4,1	20	5,5	24	5,51	28	7	32	7
 Verm. water	kW	13,8	4,1	18,4	4.9	22,14	4.95	25.9	6,3	30.4	6,3
 Rendement	%	89,8	89,1	90,1	89,3	90,1	89	90	89,5	90	89
 Rookgas Temp.	°C	130	63	135	63	140	63	145	89	150	89
 Min. afv. druk	Pa	12	12	12	12	12	12	12	12	12	12
 Afvoer Diam.	mm	Ø 80		Ø 80		Ø 80		Ø 100		Ø 100	
 Inlaat Diam.	mm	Ø 50		Ø 50		Ø 50		Ø 60		Ø 60	
 CV aansluiting	Inch	3/4		3/4		3/4		3/4		3/4	
 Ketel Liter inh.	l	80		80		80		80		80	
 Pellettank Inh.	kg	17		25		25		25		25	
 Pellet diameter	mm	Ø 6		Ø 6		Ø 6		Ø 6		Ø 6	
 Verbruik / uur	kg/h	2,95	0,9	3,6	1,1	4,4	1,1	5,2	1,4	6,0	1,4
 Branduren/tank	h	15	50	16,6	54	13,6	54,5	15	57	13,3	57
 Oppervlakte	m ³	* 350		* 400		* 500		* 600		*700	
 Gewicht	kg	160		205		215		230		240	
Afmeting	HxBxD	1001x470x485		1266x611x622		1266x611x622		1324x671x675		1324x671x675	

* Verwarmbaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning.